




AT-SS-M																									
All-in-one Solar Street Lights																									
Module No.	Photo	Features & Specifications	Lighting mode																						
AT-SS-M-10W		<p><b>Features:</b> Elegant Integrated Design, Aluminum alloy case Night sensor + PIR motion sensor 120° wide lighting angle Support 3 nights after full charging. Easy to install and Auto on/off/PIR</p> <table border="1"> <tr> <td>LED</td> <td>1000Lumens, 2700K ~6500K</td> </tr> <tr> <td>Li-ion battery</td> <td>72WH</td> </tr> <tr> <td>Solar Panel (high efficiency mono)</td> <td>18V12W</td> </tr> <tr> <td>Install height</td> <td>2.5~3 meters</td> </tr> <tr> <td>Waterproof</td> <td>IP 65</td> </tr> <tr> <td>Solar charging time</td> <td>11 hours by bright sunlight</td> </tr> <tr> <td>Lighting time</td> <td>Over 3 nights</td> </tr> <tr> <td>Material</td> <td>Aluminium alloy + toughened glass</td> </tr> <tr> <td>Size</td> <td>505*227*164mm</td> </tr> <tr> <td>Work temperature</td> <td>-25°C to 65°C</td> </tr> <tr> <td>Warranty</td> <td>5 years</td> </tr> </table>	LED	1000Lumens, 2700K ~6500K	Li-ion battery	72WH	Solar Panel (high efficiency mono)	18V12W	Install height	2.5~3 meters	Waterproof	IP 65	Solar charging time	11 hours by bright sunlight	Lighting time	Over 3 nights	Material	Aluminium alloy + toughened glass	Size	505*227*164mm	Work temperature	-25°C to 65°C	Warranty	5 years	25% dim light + motion sensor (Bright lighting 30secs when people move through the light)
LED	1000Lumens, 2700K ~6500K																								
Li-ion battery	72WH																								
Solar Panel (high efficiency mono)	18V12W																								
Install height	2.5~3 meters																								
Waterproof	IP 65																								
Solar charging time	11 hours by bright sunlight																								
Lighting time	Over 3 nights																								
Material	Aluminium alloy + toughened glass																								
Size	505*227*164mm																								
Work temperature	-25°C to 65°C																								
Warranty	5 years																								
AT-SS-M-20W		<p><b>Features:</b> Elegant Integrated Design, Aluminum alloy case Night sensor + PIR motion sensor 120° wide lighting angle Support 3 nights after full charging. Easy to install and Auto on/off/PIR</p> <table border="1"> <tr> <td>LED</td> <td>2000Lumens, 2700K ~6500K</td> </tr> <tr> <td>Li-ion battery</td> <td>144WH</td> </tr> <tr> <td>Solar Panel (high efficiency mono)</td> <td>18V25W</td> </tr> <tr> <td>Install height</td> <td>3~4 meters</td> </tr> <tr> <td>Waterproof</td> <td>IP 65</td> </tr> <tr> <td>Solar charging time</td> <td>9~10 hours by bright sunlight</td> </tr> <tr> <td>Lighting time</td> <td>Over 3 nights</td> </tr> <tr> <td>Material</td> <td>Aluminium alloy + toughened glass</td> </tr> <tr> <td>Size</td> <td>808*227*164mm</td> </tr> <tr> <td>Work temperature</td> <td>-25°C to 65°C</td> </tr> <tr> <td>Warranty</td> <td>5 years</td> </tr> </table>	LED	2000Lumens, 2700K ~6500K	Li-ion battery	144WH	Solar Panel (high efficiency mono)	18V25W	Install height	3~4 meters	Waterproof	IP 65	Solar charging time	9~10 hours by bright sunlight	Lighting time	Over 3 nights	Material	Aluminium alloy + toughened glass	Size	808*227*164mm	Work temperature	-25°C to 65°C	Warranty	5 years	25% dim light + motion sensor (Bright lighting 30secs when people move through the light)
LED	2000Lumens, 2700K ~6500K																								
Li-ion battery	144WH																								
Solar Panel (high efficiency mono)	18V25W																								
Install height	3~4 meters																								
Waterproof	IP 65																								
Solar charging time	9~10 hours by bright sunlight																								
Lighting time	Over 3 nights																								
Material	Aluminium alloy + toughened glass																								
Size	808*227*164mm																								
Work temperature	-25°C to 65°C																								
Warranty	5 years																								
AT-SS-M-30W		<p><b>Features:</b> Elegant Integrated Design, Aluminum alloy case Night sensor + PIR motion sensor 120° wide lighting angle, 12m detecting distance Support 3 nights after full charging Easy to install and Auto on/off/PIR</p> <table border="1"> <tr> <td>LED</td> <td>3000Lumens, 2700K ~6500K</td> </tr> <tr> <td>Li-ion battery</td> <td>252WH</td> </tr> <tr> <td>Solar Panel (high efficiency mono)</td> <td>18V35W</td> </tr> <tr> <td>Install height</td> <td>4~5 meters</td> </tr> <tr> <td>Waterproof</td> <td>IP 65</td> </tr> <tr> <td>Solar charging time</td> <td>9~10 hours by bright sunlight</td> </tr> <tr> <td>Lighting time</td> <td>Over 3 nights</td> </tr> <tr> <td>Material</td> <td>Aluminium alloy + toughened glass</td> </tr> <tr> <td>Size</td> <td>1098*227*164mm</td> </tr> <tr> <td>Work temperature</td> <td>-25°C to 65°C</td> </tr> <tr> <td>Warranty</td> <td>5 years</td> </tr> </table>	LED	3000Lumens, 2700K ~6500K	Li-ion battery	252WH	Solar Panel (high efficiency mono)	18V35W	Install height	4~5 meters	Waterproof	IP 65	Solar charging time	9~10 hours by bright sunlight	Lighting time	Over 3 nights	Material	Aluminium alloy + toughened glass	Size	1098*227*164mm	Work temperature	-25°C to 65°C	Warranty	5 years	25% dim light + motion sensor (Bright lighting 30secs when people move through the light)
LED	3000Lumens, 2700K ~6500K																								
Li-ion battery	252WH																								
Solar Panel (high efficiency mono)	18V35W																								
Install height	4~5 meters																								
Waterproof	IP 65																								
Solar charging time	9~10 hours by bright sunlight																								
Lighting time	Over 3 nights																								
Material	Aluminium alloy + toughened glass																								
Size	1098*227*164mm																								
Work temperature	-25°C to 65°C																								
Warranty	5 years																								

<p>AT-SS-M-60W</p>		<p><b>Features:</b>  Elegant Integrated Design, Aluminum alloy case  Constant current output!  Night sensor + PIR motion sensor  PIR 120° wide detecting angle, 12m detecting distance  Support 3 nights after full charging  Easy to install and Auto on/off/PIR</p> <table border="1"> <tr> <td><b>LED</b></td> <td>6000Lumens, 2700K ~6500K</td> </tr> <tr> <td><b>Li-ion battery</b></td> <td>360WH</td> </tr> <tr> <td><b>Solar Panel (high efficiency mono)</b></td> <td>18V60W</td> </tr> <tr> <td><b>Install height</b></td> <td>4~6 meters</td> </tr> <tr> <td><b>Waterproof</b></td> <td>IP 65</td> </tr> <tr> <td><b>Solar charging time</b></td> <td>10 hours by bright sunlight</td> </tr> <tr> <td><b>Lighting time</b></td> <td>Over 3 nights</td> </tr> <tr> <td><b>Material</b></td> <td>Aluminium alloy + toughened glass</td> </tr> <tr> <td><b>Size</b></td> <td>1553*420.5*224.5 mm</td> </tr> <tr> <td><b>Work temperature</b></td> <td>-25°C to 65°C</td> </tr> <tr> <td><b>Warranty</b></td> <td>5 years</td> </tr> </table>	<b>LED</b>	6000Lumens, 2700K ~6500K	<b>Li-ion battery</b>	360WH	<b>Solar Panel (high efficiency mono)</b>	18V60W	<b>Install height</b>	4~6 meters	<b>Waterproof</b>	IP 65	<b>Solar charging time</b>	10 hours by bright sunlight	<b>Lighting time</b>	Over 3 nights	<b>Material</b>	Aluminium alloy + toughened glass	<b>Size</b>	1553*420.5*224.5 mm	<b>Work temperature</b>	-25°C to 65°C	<b>Warranty</b>	5 years	<p>25% dim light + motion sensor  (Bright lighting 30secs when people move through the light)</p>		
<b>LED</b>	6000Lumens, 2700K ~6500K																										
<b>Li-ion battery</b>	360WH																										
<b>Solar Panel (high efficiency mono)</b>	18V60W																										
<b>Install height</b>	4~6 meters																										
<b>Waterproof</b>	IP 65																										
<b>Solar charging time</b>	10 hours by bright sunlight																										
<b>Lighting time</b>	Over 3 nights																										
<b>Material</b>	Aluminium alloy + toughened glass																										
<b>Size</b>	1553*420.5*224.5 mm																										
<b>Work temperature</b>	-25°C to 65°C																										
<b>Warranty</b>	5 years																										
<p>AT-SS-M-80W</p>		<p><b>Features:</b>  Elegant Integrated Design, Aluminum alloy case  Night sensor + PIR motion sensor  PIR 120° wide detecting angle, 12m detecting distance  Support 3 nights after full charging  Easy to install and Auto on/off/PIR.</p> <table border="1"> <tr> <td><b>LED</b></td> <td>8000Lumens, 2700K ~6500K</td> </tr> <tr> <td><b>Li-ion battery</b></td> <td>480WH</td> </tr> <tr> <td><b>Solar Panel (high efficiency mono)</b></td> <td>18V80W</td> </tr> <tr> <td><b>Install height</b></td> <td>6~8 meters</td> </tr> <tr> <td><b>Waterproof</b></td> <td>IP 65</td> </tr> <tr> <td><b>Solar charging time</b></td> <td>10 hours by bright sunlight</td> </tr> <tr> <td><b>Lighting time</b></td> <td>Over 3 nights</td> </tr> <tr> <td><b>Material</b></td> <td>Aluminium alloy + toughened glass</td> </tr> <tr> <td><b>Size</b></td> <td>1933*420.5*224.5mm</td> </tr> <tr> <td><b>Work temperature</b></td> <td>-25°C to 65°C</td> </tr> <tr> <td><b>Distance of two lights</b></td> <td>25 meters</td> </tr> <tr> <td><b>Warranty</b></td> <td>5 years</td> </tr> </table>	<b>LED</b>	8000Lumens, 2700K ~6500K	<b>Li-ion battery</b>	480WH	<b>Solar Panel (high efficiency mono)</b>	18V80W	<b>Install height</b>	6~8 meters	<b>Waterproof</b>	IP 65	<b>Solar charging time</b>	10 hours by bright sunlight	<b>Lighting time</b>	Over 3 nights	<b>Material</b>	Aluminium alloy + toughened glass	<b>Size</b>	1933*420.5*224.5mm	<b>Work temperature</b>	-25°C to 65°C	<b>Distance of two lights</b>	25 meters	<b>Warranty</b>	5 years	<p>25% dim light + motion sensor  (Bright lighting 30secs when people move through the light)</p>
<b>LED</b>	8000Lumens, 2700K ~6500K																										
<b>Li-ion battery</b>	480WH																										
<b>Solar Panel (high efficiency mono)</b>	18V80W																										
<b>Install height</b>	6~8 meters																										
<b>Waterproof</b>	IP 65																										
<b>Solar charging time</b>	10 hours by bright sunlight																										
<b>Lighting time</b>	Over 3 nights																										
<b>Material</b>	Aluminium alloy + toughened glass																										
<b>Size</b>	1933*420.5*224.5mm																										
<b>Work temperature</b>	-25°C to 65°C																										
<b>Distance of two lights</b>	25 meters																										
<b>Warranty</b>	5 years																										